

2023  
KX™ 65



MSRP  
\$3,999



| POWER                           |                                                                                                                | Front Brakes                         | Single 180mm disc with single-piston caliper |
|---------------------------------|----------------------------------------------------------------------------------------------------------------|--------------------------------------|----------------------------------------------|
| Engine                          | 2-stroke single, liquid-cooled                                                                                 | Rear Brakes                          | Single 180mm disc with single-piston caliper |
| Displacement                    | 64cc                                                                                                           | DETAILS                              |                                              |
| Bore x Stroke                   | 45.5 x 41.6mm                                                                                                  | Frame Type                           | High-tensile steel semi-double cradle        |
| Compression Ratio               | 8.4:1                                                                                                          | Rake/Trail                           | 27° / 2.4 in                                 |
| Fuel System                     | 24mm Mikuni carburetor                                                                                         | Overall Length                       | 62.6 in                                      |
| Ignition                        | CDI with Digital Advance                                                                                       | Overall Width                        | 29.9 in                                      |
| Transmission                    | 6-speed, return shift, with wet multi-disc manual clutch                                                       | Overall Height                       | 37.6 in                                      |
| Final Drive                     | Chain                                                                                                          | Ground Clearance                     | 12.0 in                                      |
| PERFORMANCE                     |                                                                                                                | Seat Height                          | 29.9 in                                      |
| Front Suspension / Wheel Travel | 33mm leading axle telescopic fork with 4-way rebound damping/8.3 in                                            | Curb Weight                          | 132.2 lb*                                    |
| Rear Suspension / Wheel Travel  | Uni-Trak® single shock system with stepless 3-turns rebound damping and fully adjustable spring preload/9.4 in | Fuel Capacity                        | 1.0 gal                                      |
| Front Tire                      | 60/100-14                                                                                                      | Wheelbase                            | 44.1 in                                      |
| Rear Tire                       | 80/100-12                                                                                                      | Color Choices                        | Lime Green                                   |
|                                 |                                                                                                                | Warranty                             | Not Available                                |
|                                 |                                                                                                                | Kawasaki Protection Plus™ (optional) | Not Available                                |

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.