











POWER

Engine 2-stroke single with exhaust power valve (KIPS), liquid-cooled

Displacement 84cc

Bore x Stroke 48.5 x 45.8mm

Compression Ratio

10.9:1 (low speed) - 9.0:1 (high speed)

36mm inverted telescopic cartridge fork with

Uni-Trak® single shock system with 24-way compression and 21-way rebound damping,

20-way compression damping/10.8 in

plus adjustable spring preload/10.8 in

28mm Keihin carburetor **Fuel System**

CDI with Digital Advance Ignition

Transmission 6-speed, return shift, with wet multi-disc

manual clutch

Final Drive Chain

PERFORMANCE

Front Brakes

Single 220mm petal disc with dual-piston

caliper

Rear Brakes

Single 184mm petal disc with single-piston

caliper

DETAILS

High-tensile steel perimeter design with **Frame Type** subframe member

Rake/Trail 29°/3.8 in

Overall Length 72.0 in

Overall Width 30.1 in

Overall Height 43.3 in

Ground 11.4 in

Clearance

Seat Height 32.7 in

Curb Weight 165.3 lb*

Fuel Capacity 1.32 gal

Wheelbase 49.8 in

Color Choices Lime Green

Not Available

Not Available

Protection Plus™ (optional)

Warranty

Kawasaki

Front Tire Rear Tire

Front

Suspension /

Wheel Travel

Rear Suspension

/ Wheel Travel

90/100-14





70/100-17