KX[™]250X











D	N	V	M	С	D
Г	U	٧	٧	C	П

Engine 4-stroke single, DOHC, liquid-cooled

Displacement 249cc

Bore x Stroke 78.0 x 52.2mm

Compression

Ratio

DFI® with 44mm Keihin throttle body and dual **Fuel System**

injectors

14.1:1

Digital CDI Ignition

Transmission 5-speed, return shift, with wet multi-disc

manual clutch

Final Drive Chain

Electronic Rider

Aids

Launch Control Mode

PERFORMANCE

Front Suspension / **Wheel Travel** 48mm inverted telescopic coil-spring fork with 23-way compression damping and 20-way

rebound damping/12.4 in

Rear Suspension / Wheel Travel

Uni-Trak® with dual-range (2.25 turns high speed/21-way low-speed) compression damping, 38-way rebound damping and

adjustable preload/12.4 in

Front Tire

Rear Tire 110/100-18

Front Brakes Single semi-floating 270mm Braking petal disc

with dual-piston caliper

Rear Brakes Single 240mm Braking petal disc with single-

piston caliper

DETAILS

Aluminum perimeter **Frame Type**

27.8° / 4.8 in Rake/Trail

Overall Length 85.4 in

Overall Width 32.3 in

Overall Height 49.6 in

13.0 in Ground

Clearance

Protection

Plus™ (optional)

Seat Height 37.2 in

Curb Weight 230.1 lb* without fuel / 240.2 lb*

Fuel Capacity 1.64 gal

Wheelbase 58.3 in

Color Choices Lime Green

Warranty Not Available

Not Available Kawasaki

80/100-21



