MULE PRO-MX™ EPS CAMO





\$14,799



TRUETIMBER® STRATA



POWER

Engine 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled

Displacement 695cc

Maximum Torque 42.7 lb-ft @ 5,000 rpm

Bore x Stroke 102.0 x 85.0mm

Compression Ratio

Fuel System DFI® with 44mm throttle body

Continuously Variable Transmission (CVT) with centrifugal Transmission

clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft Dual mode rear differential with

differential lock

Engine Braking Yes

Alternator Output 35.7 amp

(max)

Turning Radius Cargo Bed 33.4 x 44.1 x 9.1 in

Dimensions (LxWxH)

Cargo Bed Load Capacity

Fuel Capacity

Payload Capacity 1,200 lb

Seating Capacity

1,500 lb

Towing Capacity

9.5 gal

14.0 ft

Lighting (2) Halogen headlights. (2) LED headlights

699 lb / 600 lb CA Model

Front Suspension / **Wheel Travel**

CAPABILITY

Double wishbone/8.6 in

Rear Suspension / **Wheel Travel**

Double wishbone/9.1 in

25 x 10.00-12, radial **Front Tires Rear Tires** 25 x 10.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Independent, Mechanical Disc

Front Brakes Dual Disc, 2 piston caliper **Rear Brakes** Dual Disc, 1 piston caliper

Ground Clearance 10.6 in

DETAILS

Overall Length 110.0 in **Overall Width** 60.0 in

Overall Height 75.8 in

Curb Weight 1,598.6 lb* / 1,600.6 lb* CA Model

Wheelbase 78.9 in

Multi-function display includes digital speedometer, fuel Instruments gauge, odometer, hour meter, clock, dual trip meters,

2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder

lamps

Roof

Wheel Type Steel

Additional Features

Color Choices TRUETIMBER® STRATA

Warranty Kawasaki STRONG 3-Year Limited Warranty

Kawasaki Protection 12, 24, 36, or 48 months Plus™ (optional)

Scan with camera to view videos, key features and more.

Park Brake Type





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.