2024 **Z H2 SE ABS**







METALLIC MATTE GRAPHENESTEEL GRAY/EBONY/ MIRROR COATED BLACK



POWER

Engine	4-stroke, 4-cylinder, DOHC, 16-valve, liquid-cooled, supercharged	
Displacement	998cc	
Bore x Stroke	76.0 x 55.0mm	
Compression Ratio	11.2:1	
Maximum Torque	101.0 lb-ft	
Fuel System	DFI® with 40mm throttle bodies	
Ignition	TCBI with Digital Advance	
Transmission	6-speed dog-ring, return shift	
Final Drive	Sealed chain	
Electronic Rider Aids	Kawasaki Electronic Control Suspension (KECS) with Showa Skyhook Technology, KECS Linked Integrated Riding Modes, Kawasaki Cornering Management Function (KCMF), Power Modes (3), Kawasaki Launch Control Mode (KLCM), Kawasaki TRaction Control (KTRC), Kawasaki Launch Control Mode (KLCM), Kawasaki Engine Brake Control (KEBC), Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Quick Shifter (KQS) (upshift & downshift), Electronic Cruise Control	
PERFORMANCE		

Front Tire	120/70-17
Rear Tire	190/55-17
Front Brakes	Dual 320mm Disc w/Radial-mount Brembo M4.32 Calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)
Rear Brakes	Single 260mm disc with single-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS)

DETAILS

Frame Type	Trellis, high tensile steel
Rake/Trail	24.9°/4.1in
Overall Length	82.1 in
Overall Width	31.9 in
Overall Height	44.5 in
Ground Clearance	5.5 in
Seat Height	32.7 in
Curb Weight	531.4 lb*
Fuel Capacity	5.0 gal
Wheelbase	57.3 in
Special Features	Smartphone Connectivity via RIDEOLOGY THE APP, TFT Instrumentation
Color Choices	Metallic Matte Graphenesteel Gray/Ebony/Mirror Coated Black
Warranty	12 Month Limited Warranty
Kawasaki Protection Plus™ (optional)	12, 24, 36 or 48 months

.RFURMANU

Front Suspension / Wheel Travel	Showa SFF-BP Fork with KECS Compression and KECS Rebound Damping, plus Manual Spring Preload Adjustability/4.7 in
Rear Suspension / Wheel Travel	Uni-Trak®, Showa Gas-Charged Shock with KECS Compression and KECS Damping, plus Manual Spring Preload Adjustability/5.3 in

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.