

2023

MULE PRO-FXT™ EPS

Kawasaki

Let the Good Times Roll®



MSRP

\$15,899

BRIGHT WHITE

TIMBERLINE GREEN



POWER		Fuel Capacity	
Engine	4-stroke, 3-cylinder, DOHC, liquid-cooled, gas	Turning Radius	16.0 ft
Displacement	812cc	Cargo Bed Dimensions (LxWxH)	42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person)
Maximum Torque	48.0 lb-ft @ 3,500 rpm	Cargo Bed Load Capacity	999 lb (3-person) / 350 lb (6-person) / 348 lb CA Model
Bore x Stroke	2.83x2.62 in	Payload Capacity	1,616.3 lb / 1,263.5 lb CA Model
Compression Ratio	9.5:1	Seating Capacity	3-person (1 row), 6 person (2 row)
Fuel System	DFI® with 34mm throttle body	Towing Capacity	2,000 lb
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	Lighting	(2) Halogen headlights.
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock	DETAILS	
Engine Braking	Yes	Overall Length	133.3 in
Alternator Output (max)	75 amp	Overall Width	64.0 in
CAPABILITY		Overall Height	77.6 in
Front Suspension / Wheel Travel	Double wishbone/8.7 in	Curb Weight	1,911.7 lb*
Rear Suspension / Wheel Travel	Double wishbone/8.5 (L) / 8.7 (R) in	Wheelbase	92.3 in
Front Tires	26x9.00-12, radial	Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps
Rear Tires	26x11.00-12, radial	Wheel Type	Steel
Steering	Electric Power Steering (EPS), Tilt steering	Color Choices	Timberline Green, Bright White
Front Brakes	Dual Disc, 2 piston caliper	Warranty	Kawasaki STRONG 3-Year Limited Warranty
Rear Brakes	Dual Disc, 1 piston caliper	Kawasaki Protection Plus™ (optional)	12, 24 or 36 months
Park Brake Type	Independent, Mechanical Disc		
Ground Clearance	10.2 in		

Scan with camera to view videos, key features and more.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE SX™ Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE J1194. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.