MULE PRO-DXT™ FE DIESEL EPS





\$19,599



BRIGHT WHITE



POWER

Engine 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement

38.3 lb-ft @ 2,400 rpm **Maximum Torque**

Bore x Stroke 2.91 x 3.03 in

Compression Ratio 23.5:1

Fuel System Bosch in-line injection pump

Continuously Variable Transmission (CVT) with (H,L,N,R) Transmission

Selectable 2WD/4WD, shaft Dual mode rear differential with **Final Drive**

Engine Braking

Alternator Output 55 amp

(max)

7.9 gal **Fuel Capacity Turning Radius** 16.0 ft

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-**Cargo Bed** Dimensions (LxWxH)

999 lb (3-person) / 350 lb (6-person)

person)

Capacity

Payload Capacity 1.574 lb

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights.

CAPABILITY

Front Suspension / Double wishbone / 8.7 in **Wheel Travel**

Double wishbone/8.5 in (L) /8.7 in (R) Rear Suspension / Wheel Travel

Front Tires 26 x 9.00-12 **Rear Tires** 26 x 11.00-12

Electric Power Steering (EPS), Tilt steering Steering

Front Brakes Dual Disc, 2 piston caliper **Rear Brakes** Dual Disc, 1 piston caliper

Park Brake Type Independent, Mechanical Disc

Ground Clearance 10.2 in **DETAILS**

Cargo Bed Load

Overall Length 133.3 in

Overall Width 64.0 in **Overall Height** 79.5 in

Curb Weight 1,971.3 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters,

2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking

indicators, seatbelt reminder lamps

Wheel Type

Additional Features Roof, Horn, Universal Key, High Visibility Orange Seatbelts

Color Choices Bright White

Warranty Kawasaki STRONG 3-Year Limited Warranty

Kawasaki Protection 12, 24, 36, or 48 months Plus™ (optional)

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.