

2024

TERYX4™ S CAMO



BASE MSRP

\$16,799[†]

 TRUETIMBER® STRATA

POWER		DETAILS	
Engine	4-stroke, SOHC, 4-valve V-twin, liquid-cooled	Ground Clearance	12.2 in (max) / 11.2 in (std)
Displacement	783cc	Fuel Capacity	7.9 gal
Maximum Torque	47.0 lb-ft @ 5,500 rpm	Turning Radius	17.7 ft
Bore x Stroke	85.0 x 69.0mm	Cargo Bed Dimensions (LxWxH)	17.9 x 47.6 x 8.7 in
Compression Ratio	10.7:1	Cargo Bed Load Capacity	249 lb
Fuel System	DFI® with two 36mm Mikuni throttle bodies	Payload Capacity	1,000 lb
Ignition	TCBI with Electronic Advance	Seating Capacity	4
Starting System	Electric	Towing Capacity	1,300 lb
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)	Lighting	(4) LED headlights, (2) LED taillights, LED stoplight
Final Drive	Selectable 2WD/4WD with locking front differential, shaft		
Engine Braking	Yes		
CAPABILITY			
Front Suspension / Wheel Travel	Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression damping/10.7 in	Frame	Steel Tube Double-X Reinforcement
Rear Suspension / Wheel Travel	Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression damping/10.0 in	Overall Length	125.4 in
Front Tires	Maxxis® 27 x 9-14	Overall Width	62.6 in
Rear Tires	Maxxis® 27 x 11-14	Overall Height	80.5 in
Steering	Electric Power Steering (EPS) / rack-and-pinion	Curb Weight	1,638.3 lb* / 1,640.5 lb* CA Model
Front Brakes	Dual hydraulic discs with two-piston calipers	Wheelbase	88.2 in
Rear Brakes	Sealed, oil-bathed, multi-disc	Instruments	Multi-function digital meter with speedometer, fuel gauge, clock, hour meter, odometer, dual trip meter and parking-brake indicator, R/N/P/4WD, water temp and low-oil-pressure indicators
		Wheel Type	Alloy
		Additional Features	Roof
		Color Choices	TRUETIMBER® STRATA

Scan with camera to view videos, key features and more.



[†]Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2026 Kawasaki Motors Corp., U.S.A.

™/® & © 2026 TrueTimber Outdoors Holding Company, LLC. Manufactured and/or distributed under official license by Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.