

2025

# MULE PRO-MX™ LE



**MSRP  
\$14,699**



## POWER

<b>Engine</b>	4-stroke, single cylinder, SOHC, 4-valve, liquid-cooled
<b>Displacement</b>	695cc
<b>Maximum Torque</b>	42.7 lb-ft @ 5,000 rpm
<b>Bore x Stroke</b>	102.0 x 85.0mm
<b>Compression Ratio</b>	10.3:1
<b>Fuel System</b>	DFI® with 44mm throttle body
<b>Transmission</b>	Continuously Variable Transmission (CVT) with centrifugal clutch, (H,L,N,R)
<b>Final Drive</b>	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
<b>Engine Braking</b>	Yes
<b>Alternator Output (max)</b>	35.7 amp

## CAPABILITY

<b>Front Suspension / Wheel Travel</b>	Double wishbone/8.6 in
<b>Rear Suspension / Wheel Travel</b>	Double wishbone/9.1 in
<b>Front Tires</b>	25 x 8-12, radial
<b>Rear Tires</b>	25 x 10-12, radial
<b>Steering</b>	Electric Power Steering (EPS), Tilt steering
<b>Front Brakes</b>	Dual disc, 2-piston caliper
<b>Rear Brakes</b>	Dual disc, 1-piston caliper

<b>Park Brake Type</b>	Independent, mechanical disc
<b>Ground Clearance</b>	10.6 in
<b>Fuel Capacity</b>	9.5 gal
<b>Turning Radius</b>	14.0 ft
<b>Cargo Bed Dimensions (LxWxH)</b>	33.4 x 44.1 x 9.1 in
<b>Cargo Bed Load Capacity</b>	699 lb / 600 lb CA Model
<b>Payload Capacity</b>	1,200 lb / 1,100 lb CA Model
<b>Seating Capacity</b>	2
<b>Towing Capacity</b>	1,500 lb
<b>Lighting</b>	(2) Halogen headlights, (2) LED headlights

## DETAILS

<b>Overall Length</b>	110.0 in
<b>Overall Width</b>	60.0 in
<b>Overall Height</b>	75.8 in
<b>Curb Weight</b>	1,594.2 lb* / 1,596.4 lb* CA Model
<b>Wheelbase</b>	78.9 in
<b>Instruments</b>	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder lamps
<b>Additional Features</b>	Roof, Cast Aluminum Wheels
<b>Color Choices</b>	Deep Blue

Scan with camera  
to view videos,  
key features  
and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

**Kawasaki**  
Let the Good Times Roll®