NINJA® 1100SX SE ABS





MSRP **\$15,399**

EMERALD BLAZED GREEN/METALLIC DIABLO BLACK/METALLIC GRAPHITE GRAY



Front Tire

Rear Tire

Front Brakes

Rear Brakes

DETAILS

Frame Type

Rake/Trail

Overall Length

Overall Width

Overall Height

Seat Height

Weight

Estimated Dry

Curb Weight

Fuel Capacity

Ground Clearance

EMERALD BLAZED GREEN/METALLIC DIABLO BLACK

Dual 300mm discs with radial-mount 4-piston Brembo

M4.32 monobloc calipers, Kawasaki Intelligent anti-lock

Single 260mm disc with single-piston caliper, Kawasaki

Intelligent anti-lock Brake System (KIBS)



120/70-17

190/50-17

Brake System (KIBS)

Twin-spar aluminum

24.0°/3.9 in

82.7 in

31.7 in

5.3 in

32.3 in

469.7 lb**

516.0 lb*

5.0 gal

56.7 in

POWER

Engine 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-

cooled

Displacement 1,099cc

Bore x Stroke 77.0 x 59.0mm

Compression Ratio 11.8:

Maximum 134.0 hp¹ @ 9,000 rpm Horsepower

Maximum Torque 83.2 lb-ft @ 7,600 rpm

Fuel System DFI® with 38mm Electronic Throttle Valves

Ignition TCBI with Digital Advance

Transmission 6-speed, return shift with wet multi-disc manual Assist

& Slipper Clutch

Final Drive Sealed chain

Electronic Rider

Aids

Kawasaki TRaction Control (KTRC), Kawasaki Intelligent anti-lock Brake System (KIBS), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-

Enhanced Chassis Orientation Awareness

PERFORMANCE

Front Suspension / Wheel Travel

41mm inverted telescopic Showa fork with compression and rebound damping, adjustable spring preload/4.7 in

Economical Riding Indicator, Electronic Cruise Control,

Rear Suspension / Wheel Travel

Horizontal back-link, Öhlins S46 gas-charged rear shock with rebound damping, remotely adjustable spring preload/5.6 in

Wheelbase
Special Features

cial Features 4.3" All-digital TFT Instrumentation, All-LED lighting, USB

46.9 in/48.2 in w/ windshield high

Type-C outlet, Grip heaters, Smartphone Connectivity with Voice Command via RIDEOLOGY THE APP

MOTORCYCLE

Color Choices Emerald Blazed Green/Metallic Diablo Black

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.