

2025

NINJA® 500 SE KRT EDITION ABS

Kawasaki

Let the Good Times Roll®



BASE MSRP ABS

\$6,399\*

LIME GREEN/EBONY/PEARL BLIZZARD WHITE

| POWER                           |                                                            | Front Brakes         | Single 310mm semi-floating disc with 2-piston calipers and ABS                                                                                                               |
|---------------------------------|------------------------------------------------------------|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Engine                          | 4-stroke, Parallel Twin, DOHC, liquid-cooled               | Rear Brakes          | Single 220mm disc with single-piston caliper and ABS                                                                                                                         |
| Displacement                    | 451cc                                                      | DETAILS              |                                                                                                                                                                              |
| Bore x Stroke                   | 70.0 x 58.6mm                                              | Frame Type           | Trellis, high-tensile steel                                                                                                                                                  |
| Compression Ratio               | 11.3:1                                                     | Rake/Trail           | 24.7° / 3.6 in                                                                                                                                                               |
| Maximum Horsepower              | 51.0 hp <sup>1</sup> @ 10,000 rpm                          | Overall Length       | 78.5 in                                                                                                                                                                      |
| Maximum Torque                  | 31.7 lb-ft @ 7,500 rpm                                     | Overall Width        | 28.7 in                                                                                                                                                                      |
| Fuel System                     | DFI® with dual 32mm throttle bodies                        | Overall Height       | 46.5 in                                                                                                                                                                      |
| Ignition                        | TCBI with Digital Advance                                  | Ground Clearance     | 5.7 in                                                                                                                                                                       |
| Transmission                    | 6-speed                                                    | Seat Height          | 30.9 in                                                                                                                                                                      |
| Final Drive                     | Sealed chain                                               | Estimated Dry Weight | 348.4 lb** / 350.6 lb** 50-State Model                                                                                                                                       |
| Electronic Rider Aids           | Economical Riding Indicator, Anti-lock Brake System (ABS)  | Curb Weight          | 379.3 lb* / 381.5 lb* 50-State Model                                                                                                                                         |
| PERFORMANCE                     |                                                            | Fuel Capacity        | 3.7 gal                                                                                                                                                                      |
| Front Suspension / Wheel Travel | 41mm hydraulic telescopic fork/4.7 in                      | Wheelbase            | 54.1 in                                                                                                                                                                      |
| Rear Suspension / Wheel Travel  | Horizontal back-link with adjustable spring preload/5.1 in | Special Features     | ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDELOGY THE APP, Kawasaki's Intelligent Proximity Activation Start System (KIPASS), USB-C outlet |
| Front Tire                      | 110/70-17                                                  | Color Choices        | Lime Green/Ebony/Pearl Blizzard White                                                                                                                                        |
| Rear Tire                       | 150/60-17                                                  |                      |                                                                                                                                                                              |

Scan with camera to view videos, key features and more.

<sup>1</sup>Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.