

2025

NINJA<sup>®</sup> ZX<sup>™</sup>-4RR KRT EDITION ABS

Kawasaki

Let the Good Times Roll<sup>®</sup>



BASE MSRP ABS

\$9,699<sup>+</sup>

LIME GREEN/EBONY/PEARL BLIZZARD WHITE

| POWER                           |                                                                                                                                                                  | REAR SUSPENSION / WHEEL TRAVEL |                                                                                    |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|------------------------------------------------------------------------------------|
| Engine                          | 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled                                                                                                      | Front Tire                     | 120/70-17                                                                          |
| Displacement                    | 399cc                                                                                                                                                            | Rear Tire                      | 160/60-17                                                                          |
| Bore x Stroke                   | 57.0 x 39.1mm                                                                                                                                                    | Front Brakes                   | Dual 290mm semi-floating discs with radial-mount 4-piston monobloc caliper and ABS |
| Compression Ratio               | 12.3:1                                                                                                                                                           | Rear Brakes                    | Single 220mm disc with single-piston caliper and ABS                               |
| Maximum Horsepower              | 56.0 hp <sup>1</sup> @ 11,500 rpm                                                                                                                                | DETAILS                        |                                                                                    |
| Maximum Torque                  | 26.5 lb-ft @ 11,000 rpm                                                                                                                                          | Frame Type                     | Trellis, high-tensile steel                                                        |
| Fuel System                     | DFI <sup>®</sup> with 34mm throttle valves (4)                                                                                                                   | Rake/Trail                     | 23.5° / 3.8 in                                                                     |
| Ignition                        | TCBI with Digital Advance                                                                                                                                        | Overall Length                 | 78.3 in                                                                            |
| Transmission                    | 6-speed, return shift                                                                                                                                            | Overall Width                  | 30.1 in                                                                            |
| Final Drive                     | Chain                                                                                                                                                            | Overall Height                 | 43.7 in                                                                            |
| Electronic Rider Aids           | Economical Riding Indicator, Kawasaki TRaction Control (KTRC) (3-mode), Kawasaki Quick Shifter (KQS) (dual direction), Power Modes, Anti-lock Brake System (ABS) | Ground Clearance               | 5.3 in                                                                             |
| PERFORMANCE                     |                                                                                                                                                                  | Seat Height                    | 31.5 in                                                                            |
| Front Suspension / Wheel Travel | 37mm inverted Showa fork with SFF-BP internals and spring preload adjustability/4.7 in                                                                           | Curb Weight                    | 414.5 lb*                                                                          |
|                                 |                                                                                                                                                                  | Fuel Capacity                  | 4.0 gal                                                                            |
|                                 |                                                                                                                                                                  | Wheelbase                      | 54.3 in                                                                            |
|                                 |                                                                                                                                                                  | Special Features               | 4.3" Full-color TFT Instrumentation, Smartphone Connectivity via RIDELOGY THE APP  |
|                                 |                                                                                                                                                                  | Color Choices                  | Lime Green/Ebony/Pearl Blizzard White                                              |

Scan with camera to view videos, key features and more.

<sup>+</sup>Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.

<sup>\*</sup>Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.