

2026

VULCAN® 900 CUSTOM

Kawasaki

Let the Good Times Roll®



MSRP

\$9,999

 METALLIC SPARK BLACK



POWER	
Engine	4-stroke, 55-degree V-twin, liquid-cooled
Displacement	903cc
Bore x Stroke	88.0 x 74.2mm
Compression Ratio	9.5:1
Maximum Horsepower	51 hp ¹ @ 5,500 rpm
Maximum Torque	58.3 lb-ft @ 3,500 rpm
Fuel System	DFI® with 34mm throttle bodies (2), with sub-throttle valves
Ignition	TCBI with Electronic Advance
Transmission	5-speed with positive neutral finder
Final Drive	Kevlar-reinforced belt

DETAILS	
Rear Suspension / Wheel Travel	Uni-Trak® swingarm, 7-way adjustable spring preload/4.1 in
Front Tire	80/90-21
Rear Tire	180/70-15
Front Brakes	Single 300mm hydraulic disc
Rear Brakes	Single 270mm hydraulic disc
Frame Type	Semi-double cradle, high-tensile steel
Rake/Trail	33° /7.2 in
Overall Length	94.7 in
Overall Width	35.2 in
Overall Height	44.1 in
Ground Clearance	5.5 in
Seat Height	27.0 in
Curb Weight	610.8 lb*
Fuel Capacity	5.3 gal
Wheelbase	64.8 in
Color Choices	Metallic Spark Black

PERFORMANCE	
Front Suspension / Wheel Travel	41mm Showa telescopic fork/5.9 in

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.