

2026

KLR® 650 S

Kawasaki
Let the Good Times Roll®



- BASE MSRP NON-ABS

\$6,999[†]
- BASE MSRP ABS

\$7,299[†]
- 

PEARL SOLAR YELLOW

BASE MSRP \$6,999[†] NON-ABS / BASE MSRP \$7,299[†] ABS
- 

METALLIC SPARK BLACK

BASE MSRP \$6,999[†] NON-ABS / BASE MSRP \$7,299[†] ABS

POWER		Front Tire	90/90-21
Engine	4-stroke, single cylinder, DOHC	Rear Tire	130/80-17
Displacement	652cc	Front Brakes	Single 300mm disc with 2-piston calipers (and ABS)
Bore x Stroke	100.0 x 83.0mm	Rear Brakes	Single 240mm disc with single-piston caliper (and ABS)
Compression Ratio	9.8:1	DETAILS	
Maximum Horsepower	40 hp ¹ @ 6,000 rpm	Frame Type	Tubular, semi-double cradle
Maximum Torque	39.1 lb-ft @ 4,500 rpm	Rake/Trail	29.5° / 4.6 in
Fuel System	DFI® with 40mm throttle body	Overall Length	88.8 in
Ignition	CDI	Overall Width	38.2 in
Transmission	5-speed, return shift with wet multi-disc manual clutch	Overall Height	56.3/54.9 in (screen hi/lo)
Final Drive	Sealed chain	Ground Clearance	7.3 in
Electronic Rider Aids	Anti-lock Brake System (ABS)	Seat Height	32.1 in
PERFORMANCE		Estimated Dry Weight	416.6 lb** (ABS), 412.1 lb** (non-ABS)
Front Suspension / Wheel Travel	41mm telescopic fork/ 6.7 in	Curb Weight	460.6 lb* (ABS), 456.2 lb* (non-ABS)
Rear Suspension / Wheel Travel	Uni-Trak® single shock with adjustable rebound damping and adjustable spring preload/7.0 in	Fuel Capacity	6.1 gal
		Wheelbase	59.6 in
		Color Choices	Pearl Solar Yellow, Metallic Spark Black

Scan with camera
to view videos,
key features
and more.



[†]Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.