

2026

KLX®140R L



MSRP
\$4,099

- LIME GREEN
- BRIGHT WHITE



POWER		Rear Tire	90/100-16
Engine	4-stroke, single-cylinder, SOHC, air-cooled	Front Brakes	Single 220mm petal disc with a dual-piston caliper
Displacement	144cc	Rear Brakes	Single 186mm petal disc with single-piston caliper
Bore x Stroke	58.0 x 54.4mm	DETAILS	
Compression Ratio	9.5:1	Frame Type	High-tensile steel, box-section perimeter
Fuel System	Keihin PB20 carburetor	Rake/Trail	27.0° / 3.8 in
Ignition	Digital DC-CDI	Overall Length	74.6 in
Transmission	5-speed, return shift, with wet multi-disc manual clutch	Overall Width	31.1 in
Final Drive	Chain	Overall Height	42.3 in
PERFORMANCE		Ground Clearance	10.0 in
Front Suspension / Wheel Travel	33mm telescopic fork/7.1 in	Seat Height	31.5 in
Rear Suspension / Wheel Travel	Uni-Trak® linkage system and single shock with piggyback reservoir, fully adjustable preload and 22-way rebound damping/7.1 in	Estimated Dry Weight	196.2 lb**
Front Tire	70/100-19	Curb Weight	209.4 lb*
		Fuel Capacity	1.5 gal
		Wheelbase	50.6 in
		Color Choices	Lime Green, Bright White

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.