

2026

KLX[®]230 S

Kawasaki
Let the Good Times Roll[®]



BASE MSRP NON-ABS
\$5,199[†]

BASE MSRP ABS
\$5,499[†]



LIME GREEN
BASE MSRP \$5,199[†] NON-ABS / BASE MSRP \$5,499[†] ABS



BRIGHT WHITE
BASE MSRP \$5,199[†] NON-ABS / BASE MSRP \$5,499[†] ABS

POWER

Engine	4-stroke single, SOHC, air-cooled
Displacement	233cc
Bore x Stroke	67.0 x 66.0mm
Compression Ratio	9.4:1
Maximum Horsepower	17 hp ¹ @ 8,000 rpm
Maximum Torque	13.0 lb-ft @ 6,400 rpm
Fuel System	DFI [®] with 32mm throttle body
Ignition	TCBI with Electronic Advance
Transmission	6-speed
Final Drive	Sealed chain
Electronic Rider Aids	Anti-lock Brake System (ABS)

PERFORMANCE

Front Suspension / Wheel Travel	37mm telescopic fork/7.9 in
Rear Suspension / Wheel Travel	Uni-Trak [®] linkage system and single shock with adjustable spring preload/8.8 in
Front Tire	2.75 x 21

Rear Tire	4.10 x 18
Front Brakes	Single 240mm (265mm ABS Model) petal disc with a dual-piston caliper (and ABS)
Rear Brakes	Single 220mm petal disc with single-piston caliper (and ABS)

DETAILS

Frame Type	Perimeter, high-tensile steel
Rake/Tail	24.6° / 3.8 in
Overall Length	81.9 in
Overall Width	33.3 in
Overall Height	44.9 in
Ground Clearance	9.4 in
Seat Height	33.3 in
Estimated Dry Weight	277.7 lb** (ABS), 275.5 lb** (non-ABS) 50-State Model; 275.6 lb** (ABS), 273.4 lb** (non-ABS) 49-State Model
Curb Weight	293.3 lb* (ABS), 291.1 lb* (non-ABS) 50-State Model; 291.1 lb* (ABS), 288.9 lb* (non-ABS) 49-State Model
Fuel Capacity	2.0 gal
Wheelbase	53.7 in
Special Features	ERGO-FIT [®] , LCD Instrumentation with Smartphone Connectivity via RIDELOGY THE APP MOTORCYCLE
Color Choices	Lime Green, Bright White

Scan with camera
to view videos,
key features
and more.



[†]Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.
^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
^{**}Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.