

2026

KX™ 250X



BASE MSRP NON-ABS  
\$9,199<sup>†</sup>



| POWER                           |                                                                                                                                            | Front Tire       | 80/100-21                                                              |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|------------------|------------------------------------------------------------------------|
| Engine                          | 4-stroke, single-cylinder, DOHC, liquid-cooled                                                                                             | Rear Tire        | 110/100-18                                                             |
| Displacement                    | 249cc                                                                                                                                      | Front Brakes     | Single semi-floating 270mm Braking petal disc with dual-piston caliper |
| Bore x Stroke                   | 78.0 x 52.2mm                                                                                                                              | Rear Brakes      | Single 240mm Braking petal disc with single-piston caliper             |
| Compression Ratio               | 14.0:1                                                                                                                                     | DETAILS          |                                                                        |
| Fuel System                     | DFI® with 44mm Keihin throttle body and dual injectors                                                                                     | Frame Type       | Aluminum perimeter                                                     |
| Ignition                        | Digital CDI with handlebar-controlled power modes                                                                                          | Rake/Trail       | 27.8° / 4.8 in                                                         |
| Transmission                    | 5-speed, return shift, with wet multi-disc manual clutch and hydraulic clutch actuation                                                    | Overall Length   | 85.8 in                                                                |
| Final Drive                     | Chain                                                                                                                                      | Overall Width    | 32.3 in                                                                |
| Electronic Rider Aids           | Power Modes, Kawasaki TRaction Control (KTRC), Launch Control Mode                                                                         | Overall Height   | 49.6 in                                                                |
| PERFORMANCE                     |                                                                                                                                            | Ground Clearance | 13.0 in                                                                |
| Front Suspension / Wheel Travel | 49mm Showa inverted telescopic coil-spring fork with 16-way compression and rebound damping / 12.0 in                                      | Seat Height      | 37.2 in                                                                |
| Rear Suspension / Wheel Travel  | Uni-Trak® with dual-range (4 turns high speed/19-way low-speed) compression damping, 22-way rebound damping and adjustable preload/12.1 in | Curb Weight      | 233.3 lb* without fuel / 243.2 lb*                                     |
|                                 |                                                                                                                                            | Fuel Capacity    | 1.64 gal                                                               |
|                                 |                                                                                                                                            | Wheelbase        | 58.5 in                                                                |
|                                 |                                                                                                                                            | Special Features | Smartphone Connectivity via RIDELOGY THE APP KX™, ERGO-FIT®            |
|                                 |                                                                                                                                            | Color Choices    | Lime Green                                                             |



<sup>†</sup>Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.