

2026  
KX™ 65



BASE MSRP NON-ABS  
\$4,249\*



LIME GREEN

POWER

|                   |                                                          |
|-------------------|----------------------------------------------------------|
| Engine            | 2-stroke, single-cylinder, liquid-cooled                 |
| Displacement      | 64cc                                                     |
| Bore x Stroke     | 44.5 x 41.6mm                                            |
| Compression Ratio | 8.4:1                                                    |
| Fuel System       | 24mm Mikuni carburetor                                   |
| Ignition          | CDI with digital advance                                 |
| Transmission      | 6-speed, return shift, with wet multi-disc manual clutch |
| Final Drive       | Chain                                                    |

PERFORMANCE

|                                 |                                                                                                                |
|---------------------------------|----------------------------------------------------------------------------------------------------------------|
| Front Suspension / Wheel Travel | 33mm leading axle telescopic fork with 4-way rebound damping/8.3 in                                            |
| Rear Suspension / Wheel Travel  | Uni-Trak® single shock system with stepless 3-turns rebound damping and fully adjustable spring preload/9.4 in |
| Front Tire                      | 60/100-14                                                                                                      |

|              |                                              |
|--------------|----------------------------------------------|
| Rear Tire    | 80/100-12                                    |
| Front Brakes | Single 180mm disc with single-piston caliper |
| Rear Brakes  | Single 180mm disc with single-piston caliper |

DETAILS

|                  |                                       |
|------------------|---------------------------------------|
| Frame Type       | High-tensile steel semi-double cradle |
| Rake/Trail       | 27.0° / 2.4 in                        |
| Overall Length   | 62.6 in                               |
| Overall Width    | 29.9 in                               |
| Overall Height   | 37.6 in                               |
| Ground Clearance | 12.0 in                               |
| Seat Height      | 29.9 in                               |
| Curb Weight      | 126.1 lb* without fuel / 132.2 lb*    |
| Fuel Capacity    | 1.0 gal                               |
| Wheelbase        | 44.1 in                               |
| Color Choices    | Lime Green                            |

Scan with camera  
to view videos,  
key features  
and more.



\*Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.  
\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.  
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.