

2026

MULE PRO-FXT™ 820 EPS

Kawasaki

Let the Good Times Roll®



- BASE MSRP
\$16,999[†]
- TIMBERLINE GREEN
BASE MSRP \$16,999[†]
- DARK ROYAL RED
BASE MSRP \$16,999[†]

POWER			
Engine	4-stroke, 3-cylinder, DOHC, liquid-cooled, gas	Rear Brakes	Dual disc, 1-piston caliper
Displacement	812cc	Park Brake Type	Independent, mechanical disc
Maximum Torque	48.0 lb-ft @ 3,500 rpm	Ground Clearance	10.2 in
Bore x Stroke	72.0 x 66.5mm	Fuel Capacity	7.9 gal
Compression Ratio	9.5:1	Turning Radius	16.0 ft
Fuel System	DFI® with 34mm throttle body (3)	Cargo Bed Dimensions (LxWxH)	42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person)
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	Cargo Bed Load Capacity	999 lb (3-person)/350 lb (6-person)/348 lb CA Model
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock	Payload Capacity	1,616.3/1,263.5 lb CA Model
Engine Braking	Yes	Seating Capacity	3-person (1 row), 6 person (2 row)
Alternator Output (max)	75 amp	Towing Capacity	2,000 lb
		Lighting	(2) Halogen headlights
CAPABILITY		DETAILS	
Front Suspension / Wheel Travel	Double wishbone/8.7 in	Overall Length	133.3 in
Rear Suspension / Wheel Travel	Double wishbone/8.5 in (L)/8.7 in (R)	Overall Width	64.0 in
Front Tires	26 x 9-12, radial	Overall Height	77.6 in
Rear Tires	26 x 11-12, radial	Estimated Dry Weight	1,861.0/1,863.2 lb** CA Model
Wheel Type	Steel	Curb Weight	1,949.2/1,951.4 lb* CA Model
Steering	Rack-and-pinion w/ Electric Power Steering (EPS), Tilt steering	Wheelbase	92.3 in
Front Brakes	Dual disc, 2-piston caliper	Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt reminder lamps
		Color Choices	Timberline Green, Dark Royal Red

Scan with camera to view videos, key features and more.

[†]Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

^{**}Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.