

2026

MULE PRO-MX™ EPS



BASE MSRP

\$14,499⁺

GRAY
BASE MSRP \$14,499⁺

FIRECRACKER RED
BASE MSRP \$14,499⁺

POWER			
Engine	4-stroke, single cylinder, SOHC, 4-valve, liquid-cooled	Rear Brakes	Dual disc, 1-piston caliper
Displacement	695cc	Park Brake Type	Independent, mechanical disc
Maximum Horsepower	44.0 hp ¹ @ 6,000 rpm	Ground Clearance	10.6 in
Maximum Torque	42.7 lb-ft @ 5,000 rpm	Fuel Capacity	9.5 gal
Bore x Stroke	102.0 x 85.0mm	Turning Radius	14.0 ft
Compression Ratio	10.3:1	Cargo Bed Dimensions (LxWxH)	33.4 x 44.1 x 9.1 in
Fuel System	DFI® with 44mm throttle body	Cargo Bed Load Capacity	699 lb / 600 lb CA Model
Transmission	Continuously Variable Transmission (CVT) with centrifugal clutch, (H,L,N,R)	Payload Capacity	1,200 lb / 1,100 lb CA Model
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock	Seating Capacity	2
Engine Braking	Yes	Towing Capacity	1,500 lb
Alternator Output (max)	35.7 amp	Lighting	(2) Halogen headlights, (2) LED headlights
CAPABILITY		DETAILS	
Front Suspension / Wheel Travel	Double wishbone/8.6 in	Overall Length	110.0 in
Rear Suspension / Wheel Travel	Double wishbone/9.1 in	Overall Width	60.0 in
Front Tires	25 x 8-12, radial	Overall Height	74.4 in
Rear Tires	25 x 10-12, radial	Estimated Dry Weight	1,512.6 lb** / 1,514.8 lb** CA Model
Steering	Electric Power Steering (EPS), Tilt steering	Curb Weight	1,587.6 lb* / 1,589.8 lb* CA Model
Front Brakes	Dual disc, 2-piston caliper	Wheelbase	78.9 in
		Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder lamps
		Color Choices	Gray, Firecracker Red

Scan with camera to view videos, key features and more.

⁺Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

^{**}Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.