

2026

NINJA® 500 SE ABS

Kawasaki

Let the Good Times Roll®



MSRP

\$6,499

- LIME GREEN
- METALLIC YELLOWISH GREEN/EBONY
- METALLIC MATTE TWILIGHT BLUE/CANDY PERSIMMON RED



POWER		Front Brakes	Single 310mm semi-floating disc with 2-piston calipers and ABS
Engine	4-stroke, Parallel Twin, DOHC, liquid-cooled	Rear Brakes	Single 220mm disc with single-piston caliper and ABS
Displacement	451cc	DETAILS	
Bore x Stroke	70.0 x 58.6mm	Frame Type	Trellis, high-tensile steel
Compression Ratio	11.3:1	Rake/Trail	24.7° /3.6 in
Maximum Horsepower	51.0 hp ¹ @ 10,000 rpm	Overall Length	78.5 in
Maximum Torque	31.7 lb-ft @ 7,500 rpm	Overall Width	28.7 in
Fuel System	DFI® with dual 32mm throttle bodies	Overall Height	46.5 in
Ignition	TCBI with Digital Advance	Ground Clearance	5.7 in
Transmission	6-speed	Seat Height	30.9 in
Final Drive	Sealed chain	Estimated Dry Weight	350.6 lb** 50-State Model; 348.4 lb** 49-State Model
Electronic Rider Aids	Economical Riding Indicator, Anti-lock Brake System (ABS)	Curb Weight	381.5 lb* 50-State Model; 379.3 lb* 49-State Model
PERFORMANCE		Fuel Capacity	3.7 gal
Front Suspension / Wheel Travel	41mm hydraulic telescopic fork/4.7 in	Wheelbase	54.1 in
Rear Suspension / Wheel Travel	Horizontal back-link with adjustable spring preload/5.1 in	Special Features	ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLGY THE APP, Kawasaki's Intelligent Proximity Activation Start System (KIPASS), USB-C outlet
Front Tire	110/70-17	Color Choices	Lime Green, Metallic Yellowish Green/Ebony, Metallic Matte Twilight Blue/Candy Persimmon Red
Rear Tire	150/60-17		

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.