

2026

NINJA<sup>®</sup> ZX<sup>™</sup>-4R ABS

Kawasaki

Let the Good Times Roll<sup>®</sup>



MSRP

\$9,299

 METALLIC SPARK BLACK



| POWER                           |                                                                                                                   | Front Tire           | 120/70-17                                                                          |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------|----------------------|------------------------------------------------------------------------------------|
| Engine                          | 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled                                                       | Rear Tire            | 160/60-17                                                                          |
| Displacement                    | 399cc                                                                                                             | Front Brakes         | Dual 290mm semi-floating discs with radial-mount 4-piston monobloc caliper and ABS |
| Bore x Stroke                   | 57.0 x 39.1mm                                                                                                     | Rear Brakes          | Single 220mm disc with single-piston caliper and ABS                               |
| Compression Ratio               | 12.3:1                                                                                                            | DETAILS              |                                                                                    |
| Maximum Horsepower              | 56.0 hp <sup>1</sup> @ 11,500 rpm                                                                                 | Frame Type           | Trellis, high-tensile steel                                                        |
| Maximum Torque                  | 26.5 lb-ft @ 11,000 rpm                                                                                           | Rake/Trail           | 23.5° / 3.8 in                                                                     |
| Fuel System                     | DFI <sup>®</sup> with 34mm throttle valves (4)                                                                    | Overall Length       | 78.3 in                                                                            |
| Ignition                        | TCBI with Digital Advance                                                                                         | Overall Width        | 30.1 in                                                                            |
| Transmission                    | 6-speed, return shift                                                                                             | Overall Height       | 43.7 in                                                                            |
| Final Drive                     | Chain                                                                                                             | Ground Clearance     | 5.3 in                                                                             |
| Electronic Rider Aids           | Economical Riding Indicator, Kawasaki TRaction Control (KTRC) (3-mode), Power Modes, Anti-lock Brake System (ABS) | Seat Height          | 31.5 in                                                                            |
| PERFORMANCE                     |                                                                                                                   | Estimated Dry Weight | 383.7 lb**                                                                         |
| Front Suspension / Wheel Travel | 37mm inverted Showa fork with SFF-BP internals/4.7 in                                                             | Curb Weight          | 414.5 lb*                                                                          |
| Rear Suspension / Wheel Travel  | Horizontal back-link, Showa shock w/ adjustable spring preload/4.4 in                                             | Fuel Capacity        | 4.0 gal                                                                            |
|                                 |                                                                                                                   | Wheelbase            | 54.3 in                                                                            |
|                                 |                                                                                                                   | Special Features     | 4.3" Full-color TFT Instrumentation, Smartphone Connectivity via RIDELOGY THE APP  |
|                                 |                                                                                                                   | Color Choices        | Metallic Spark Black                                                               |

Scan with camera  
to view videos,  
key features  
and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [Kawasaki.com](#) for full product details.