

2026

NINJA® ZX™-6R

Kawasaki
Let the Good Times Roll®



BASE MSRP NON-ABS
\$11,599[†]

BASE MSRP ABS
\$12,599[‡]

-  LIME GREEN
BASE MSRP \$11,599[†] NON-ABS / BASE MSRP \$12,599[‡] ABS
-  PEARL ROBOTIC WHITE/METALLIC SPARK BLACK
BASE MSRP \$11,599[†] NON-ABS / BASE MSRP \$12,599[‡] ABS
-  METALLIC MATTE GRAPHENESTEEL GRAY/
METALLIC SPARK BLACK/PEARL STORM GRAY
BASE MSRP \$11,599[†] NON-ABS / BASE MSRP \$12,599[‡] ABS
-  METALLIC MATTE DARK GRAY/EBONY
BASE MSRP \$11,599[†] NON-ABS / BASE MSRP \$12,599[‡] ABS

POWER			
Engine	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled	Rear Tire	180/55 ZR17
Displacement	636cc	Front Brakes	Dual semi-floating 310mm discs with dual radial-mounted, monobloc, opposed 4-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only)
Bore x Stroke	67.0 x 45.1mm	Rear Brakes	Single 220mm petal discs with single-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only)
Compression Ratio	12.9:1	DETAILS	
Maximum Horsepower	127.0 hp ¹ @ 13,000 rpm	Frame Type	Aluminum perimeter
Maximum Torque	52.1 lb-ft @ 10,800 rpm	Rake/Trail	23.5°/4.0 in
Fuel System	DFI® with 38mm Keihin throttle bodies (4) and oval sub-throttles	Overall Length	79.7 in
Ignition	TCBI with electronic advance	Overall Width	28.0 in
Transmission	6-speed, return shift	Overall Height	43.3 in
Final Drive	Sealed chain	Ground Clearance	5.1 in
Electronic Rider Aids	Kawasaki Traction Control (KTRC), Power Modes (Full/Low), Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only), Kawasaki Quick Shifter (KQS) (upshift only)	Seat Height	32.7 in
PERFORMANCE		Estimated Dry Weight	394.7 lb** (ABS), 390.3 lb** (non-ABS) 50-State Model; 392.5 lb** (ABS), 388.1 lb** (non-ABS) 49-State Model
Front Suspension / Wheel Travel	41mm inverted fork Showa Separate Function Big Piston Fork (SFF-BP) with rebound and compression damping and spring preload adjustability, and top-out springs/4.7 in	Curb Weight	436.6 lb* (ABS), 432.2 lb* (non-ABS) 50-State Model; 434.4 lb* (ABS), 430.0 lb* (non-ABS) 49-State Model
Rear Suspension / Wheel Travel	Bottom-link Uni-Trak® with single shock, stepless compression damping adjustment, stepless adjustable rebound damping, fully adjustable spring preload/5.9 in	Fuel Capacity	4.5 gal
Front Tire	120/70 ZR17	Wheelbase	55.1 in
		Special Features	4.3" Full-Color TFT Instrumentation, Smartphone Connectivity via RIDELOGY THE APP
		Color Choices	Lime Green, Pearl Robotic White/Metallic Spark Black, Metallic Matte Graphenesteel Gray/Metallic Spark Black/Pearl Storm Gray, Metallic Matte Dark Gray/Ebony

Scan with camera
to view videos,
key features
and more.



[†]Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

^{**}Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.