

2026

TERYX KRX<sup>®</sup> 1000 ROCK EDITION

Kawasaki

Let the Good Times Roll<sup>®</sup>



BASE MSRP

\$25,099<sup>+</sup>

MATTE DARK BEIGE/BROWNISH ORANGE

| POWER                           |                                                                                                                                                            |                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Engine                          | 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled                                                                                                       | Ground Clearance             | 14.6 in (max) / 14.2 in (std)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Displacement                    | 999cc                                                                                                                                                      | Fuel Capacity                | 10.6 gal                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Maximum Horsepower              | 110.0 hp <sup>1</sup> @ 8,500 rpm                                                                                                                          | Turning Radius               | 20.3 ft                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Maximum Torque                  | 75.2 lb-ft @ 7,000 rpm                                                                                                                                     | Cargo Bed Dimensions (LxWxH) | 14.6 x 33.1 x 9.1 in                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Bore x Stroke                   | 92.0 x 75.1mm                                                                                                                                              | Cargo Bed Load Capacity      | 351 lb                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Compression Ratio               | 11.5:1                                                                                                                                                     | Payload Capacity             | 781 lb                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Fuel System                     | DFI <sup>®</sup> with (2) 50mm throttle bodies                                                                                                             | Seating Capacity             | 2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Ignition                        | TCBI with electronic advance                                                                                                                               | Towing Capacity              | N/A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Starting System                 | Electric                                                                                                                                                   | Lighting                     | (2) LED headlights, (2) LED taillights, LED stoplight                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Transmission                    | Automatic CVT with centrifugal clutch (H,L,N,R)                                                                                                            | DETAILS                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Final Drive                     | Selectable 2WD/4WD with locking front differential, shaft                                                                                                  | Frame                        | Ladder type, tubular steel                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Engine Braking                  | Yes                                                                                                                                                        | Overall Length               | 133.3 in                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| CAPABILITY                      |                                                                                                                                                            | Overall Width                | 70.1 in                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Front Suspension / Wheel Travel | Double wishbone, FOX 2.5 Podium LSC piggyback shocks, fully adjustable preload, and 24-position adjustable compression damping/18.6 in                     | Overall Height               | 77.8 in                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Rear Suspension / Wheel Travel  | 4-link trailing-arm rear suspension, FOX 2.5 Podium LSC piggyback shocks, fully adjustable preload, and 24-position adjustable compression damping/21.1 in | Estimated Dry Weight         | 1,953.6 lb** / 1,955.8 lb** CA Model                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Front Tires                     | Maxxis <sup>®</sup> Roxxzilla 32 x 10.00R15 8PR                                                                                                            | Curb Weight                  | 2,052.9 lb* / 2,055.1 lb* CA Model                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Rear Tires                      | Maxxis <sup>®</sup> Roxxzilla 32 x 10.00R15 8PR                                                                                                            | Wheelbase                    | 98.8 in                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Wheel Type                      | Alloy with bead-lock wheels                                                                                                                                | Instruments                  | Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp |
| Steering                        | Electric Power Steering (EPS) / rack-and-pinion                                                                                                            | Additional Features          | KQR™ Sport Roof, F/R Tow Hooks, High Molecular Weight (HMW) polyethylene skid plates & front A-arm/trailing arm guards, WARN <sup>®</sup> VRX 45-S Powersport Winch                                                                                                                                                                                                                                                                                                                                                                                                              |
| Front Brakes                    | 258mm dual hydraulic discs with 2-piston calipers                                                                                                          | Color Choices                | Matte Dark Beige/Brownish Orange                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Rear Brakes                     | 258mm dual hydraulic discs with single-piston calipers                                                                                                     |                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

Scan with camera to view videos, key features and more.



<sup>+</sup>Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.

<sup>\*</sup>Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

<sup>\*\*</sup>Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx<sup>®</sup> side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.