

2026

TERYX KRX[®] 1000 ROCK EDITION

Kawasaki

Let the Good Times Roll[®]



MSRP

\$25,099

MATTE DARK BEIGE/BROWNISH ORANGE



POWER			
Engine	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled	Fuel Capacity	10.6 gal
Displacement	999cc	Turning Radius	20.3 ft
Maximum Horsepower	110.0 hp ¹ @ 8,500 rpm	Cargo Bed Dimensions (LxWxH)	14.6 x 33.1 x 9.1 in
Maximum Torque	75.2 lb-ft @ 7,000 rpm	Cargo Bed Load Capacity	351 lb
Bore x Stroke	92.0 x 75.1mm	Payload Capacity	781 lb
Compression Ratio	11.5:1	Seating Capacity	2
Fuel System	DFI [®] with (2) 50mm throttle bodies	Towing Capacity	N/A
Ignition	TCBI with electronic advance	Lighting	(2) LED headlights, (2) LED taillights, LED sto
Starting System	Electric	DETAILS	
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)		
Final Drive	Selectable 2WD/4WD with locking front differential, shaft	Frame	Ladder type, tubular steel
Engine Braking	Yes	Overall Length	133.3 in
CAPABILITY		Overall Width	70.1 in
		Overall Height	77.8 in
Front Suspension / Wheel Travel	Double wishbone, FOX 2.5 Podium LSC piggyback shocks, fully adjustable preload, and 24-position adjustable compression damping/18.6 in	Estimated Dry Weight	1,953.6 lb** / 1,955.8 lb** CA Model
Rear Suspension / Wheel Travel	4-link trailing-arm rear suspension, FOX 2.5 Podium LSC piggyback shocks, fully adjustable preload, and 24-position adjustable compression damping/21.1 in	Curb Weight	2,052.9 lb* / 2,055.1 lb* CA Model
Front Tires	Maxxis [®] Roxxzilla 32 x 10.00R15 8PR	Wheelbase	98.8 in
Rear Tires	Maxxis [®] Roxxzilla 32 x 10.00R15 8PR	Instruments	Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp
Wheel Type	Alloy with bead-lock wheels	Additional Features	KQR [™] Sport Roof, F/R Tow Hooks, High Molecular Weight (HMW) polyethylene skid plates & front A-arm/trailing arm guards, WARN [®] VRX 45-S Powersport Winch
Steering	Electric Power Steering (EPS) / rack-and-pinion	Color Choices	Matte Dark Beige/Brownish Orange
Front Brakes	258mm dual hydraulic discs with 2-piston calipers		
Rear Brakes	258mm dual hydraulic discs with single-piston calipers		
Ground Clearance	14.6 in (max) / 14.2 in (std)		

Scan with camera to view videos, key features and more.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx[®] side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.