NEW 2026

Z1100 SE ABS





MSRP \$14,999



METALLIC MATTE GRAPHENESTEEL GRAY/ METALLIC MATTE CARBON GRAY



POWER

Engine 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled

Displacement 1,099cc

Bore x Stroke 77.0 x 59.0mm

11.8:1

Compression Ratio

Maximum

Horsepower

Maximum Torque

Fuel System

Ignition

Transmission

Final Drive

Electronic Rider Aids

134.0 hp1 @ 9,000 rpm

83.3 lb-ft @ 7,600 rpm

DFI® with 38mm throttle bodies

TCBI with Electronic Advance

6-speed, return shift

Sealed chain

Economical Riding Indicator, Electronic Cruise Control,

Kawasaki TRaction Control (KTRC), Kawasaki Intelligent anti-lock Brake System (KIBS), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-

Enhanced Chassis Orientation Awareness

PERFORMANCE

Front Suspension / **Wheel Travel**

41mm inverted telescopic fork with compression and rebound damping and spring preload adjustability/4.7 in

Rear Suspension / **Wheel Travel**

Horizontal back-link, Öhlins S46 gas-charged rear shock with rebound damping and remote spring preload

adjustability/5.4 in

Front Tire 120/70-17 **Rear Tire** 190/50-17

Front Brakes Dual 300mm semi-floating discs with radial-mount 4-

piston Brembo M4.32 monobloc calipers and ABS

Rear Brakes Single 250mm disc with single-piston caliper and ABS

DETAILS

Frame Type Twin-tube, aluminum

Rake/Trail 24.5° / 4.0 in

Overall Length 80.9 in

Overall Width 32.5 in

Overall Height 42.7 in

Ground Clearance 4.9 in

Seat Height 32.1 in

Estimated Dry Weight

487.3 lb* **Curb Weight**

Fuel Capacity 4.5 gal

Wheelbase 56.7 in

Special Features 5" All-digital TFT color instrumentation, All-LED lighting,

> USB-C outlet, Smartphone Connectivity with available Voice Command and Turn-by-Turn Navigation via

RIDEOLOGY THE APP MOTORCYCLE***

Color Choices Metallic Matte Graphenesteel Gray/Metallic Matte Carbon

443.2 lb**

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). *RIDEOLOGY THE APP and all trademarks, registered trademarks, logos, and copyrights are the property of their respective owners. Voice command and navigation functions will be available only to users who have purchased a license for those functions. Feature availability may vary to meet individual markets.

1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.