

2026

Z650 S ABS

Kawasaki
Let the Good Times Roll®



BASE MSRP ABS
\$7,699*



METALLIC MATTE GRAPHENESTEEL GRAY/
METALLIC FLAT SPARK BLACK

POWER		Rear Tire	160/60-17
Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled	Front Brakes	Dual 300mm semi-floating discs with two-piston calipers (and ABS)
Displacement	649cc	Rear Brakes	Single 220mm disc (and ABS)
Bore x Stroke	83.0 x 60.0mm	DETAILS	
Compression Ratio	10.8:1	Frame Type	Trellis, high tensile steel
Maximum Horsepower	67.0 hp ¹ @ 8,000 rpm	Rake/Trail	24.0° / 3.9 in
Maximum Torque	47.2 lb-ft @ 6,700 rpm	Overall Length	80.9 in
Fuel System	DFI® with Keihin 36mm throttle bodies	Overall Width	31.7 in
Ignition	TCBI with Electronic Advance	Overall Height	42.5 in
Transmission	6-speed, return shift	Ground Clearance	5.1 in
Final Drive	Sealed chain	Seat Height	31.7 in
Electronic Rider Aids	Economical Riding Indicator, Kawasaki TRaction Control (KTRC), Anti-lock Brake System (ABS), Kawasaki Quick Shifter (KQS) available as an accessory	Estimated Dry Weight	374.9 lb** / 377.1 lb** 50-State Model
PERFORMANCE		Curb Weight	416.7 lb* / 419.0 lb* 50-State Model
Front Suspension / Wheel Travel	41mm telescopic fork/4.9 in	Fuel Capacity	4.0 gal
Rear Suspension / Wheel Travel	Horizontal back-link with adjustable preload, swingarm/5.1 in	Wheelbase	55.5 in
Front Tire	120/70-17	Special Features	4.3-in All-digital TFT color Instrumentation, All-LED lighting, Smartphone Connectivity via RIDELOGY THE APP MOTORCYCLE, USB Type-C outlet available as an accessory
		Color Choices	Metallic Matte Graphenesteel Gray/Metallic Flat Spark Black

Scan with camera
to view videos,
key features
and more.



¹Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.
^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
^{**}Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied)
¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.