

NEW 2027

# KLX<sup>®</sup>300 DF ABS



BASE MSRP ABS  
**\$6,299\***

 MEDIUM CLOUDY GRAY

| POWER                           |                                                                                                                                         | Front Tire           | 3.0 x 21                                                                                                    |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------------------------------|
| Engine                          | 4-stroke, single-cylinder, DOHC, liquid-cooled                                                                                          | Rear Tire            | 4.6 x 18                                                                                                    |
| Displacement                    | 292cc                                                                                                                                   | Front Brakes         | Single 250mm petal disc with a dual-piston caliper and ABS                                                  |
| Bore x Stroke                   | 78.0 x 61.2mm                                                                                                                           | Rear Brakes          | Single 240mm petal disc with single-piston caliper                                                          |
| Compression Ratio               | 10.9:1                                                                                                                                  | DETAILS              |                                                                                                             |
| Maximum Horsepower              | 26.8 hp <sup>1</sup> @ 8,000 rpm                                                                                                        | Frame Type           | Tubular, semi-double cradle                                                                                 |
| Maximum Torque                  | 18.4 lb-ft @ 6,800 rpm                                                                                                                  | Rake/Trail           | 26.7° / 4.2 in                                                                                              |
| Fuel System                     | DFI <sup>®</sup> with 34mm Keihin throttle body                                                                                         | Overall Length       | TBA                                                                                                         |
| Ignition                        | CDI                                                                                                                                     | Overall Width        | TBA                                                                                                         |
| Transmission                    | 6-speed, return shift with wet multi-disc manual clutch                                                                                 | Overall Height       | TBA                                                                                                         |
| Final Drive                     | Chain                                                                                                                                   | Ground Clearance     | TBA                                                                                                         |
| Electronic Rider Aids           | Anti-lock Brake System (ABS)                                                                                                            | Seat Height          | TBA                                                                                                         |
| PERFORMANCE                     |                                                                                                                                         | Estimated Dry Weight | TBA                                                                                                         |
| Front Suspension / Wheel Travel | 43mm inverted telescopic fork with adjustable compression damping/10.0 in                                                               | Curb Weight          | TBA                                                                                                         |
| Rear Suspension / Wheel Travel  | Uni-Trak <sup>®</sup> gas charged shock with piggyback reservoir with adjustable compression, rebound damping and spring preload/9.1 in | Fuel Capacity        | 2.0 gal                                                                                                     |
|                                 |                                                                                                                                         | Wheelbase            | TBA                                                                                                         |
|                                 |                                                                                                                                         | Special Features     | LCD instrumentation with Smartphone Connectivity via RIDELOGY THE APP MOTORCYCLE, Hand guards, Rear carrier |
|                                 |                                                                                                                                         | Color Choices        | Medium Cloudy Gray                                                                                          |

Scan with camera to view videos, key features and more.

<sup>\*</sup>Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.

<sup>\*</sup>Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

<sup>\*\*</sup>Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.