

2027

MULE SX™ 4x4



- BASE MSRP

\$9,199[†]
- TIMBERLINE GREEN

BASE MSRP \$9,199[†]
- BRIGHT WHITE

BASE MSRP \$9,199[†]

POWER		DETAILS	
Engine	4-stroke, single-cylinder, OHV, air-cooled	Front Brakes	Drum
Displacement	401cc	Rear Brakes	Drum
Maximum Horsepower	13.3 hp ¹ @ 4,000 rpm	Park Brake Type	Independent, mechanical drum
Maximum Torque	21.4 lb-ft @ 2,400 rpm	Ground Clearance	6.7 in
Bore x Stroke	82.0 x 76.0mm	Fuel Capacity	4.2 gal
Compression Ratio	8.6:1	Turning Radius	10.8 ft
Fuel System	Fuel Injection	Cargo Bed Dimensions (LxWxH)	35.6 x 40.9 x 9.6 in
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	Cargo Bed Load Capacity	399 lb
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock	Payload Capacity	915 lb
Engine Braking	No	Seating Capacity	2
Alternator Output (max)	22.9 amp	Towing Capacity	1,100 lb ^{***}
CAPABILITY		Lighting	(2) Halogen headlights, tail/brake lights
Front Suspension / Wheel Travel	MacPherson Strut/3.1 in	Overall Length	106.7 in
Rear Suspension / Wheel Travel	Unit Swingarm/3.1 in	Overall Width	52.6 in
Front Tires	24 x 9-10	Overall Height	70.9 in
Rear Tires	24 x 11-10	Estimated Dry Weight	992.3 lb ^{**}
Steering	Rack-and-pinion	Curb Weight	1,031.9 lb [*]
		Wheelbase	70.1 in
		Instruments	Fuel gauge, hour meter, oil temp light, parking brake light
		Color Choices	Timberline Green, Bright White

Scan with camera to view videos, key features and more.



[†]Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

^{**}Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

^{***}Requires optional hitch.

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

All MULE SX™ Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE J1194.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.