

2027

MULE SX™ 4x4 XC LE

Kawasaki

Let the Good Times Roll®



MSRP

\$10,699

METALLIC ONYX BLACK



POWER		DETAILS	
Engine	4-stroke, single-cylinder, OHV, air-cooled	Rear Brakes	Drum
Displacement	401cc	Park Brake Type	Independent, mechanical drum
Maximum Horsepower	13.3 hp ¹ @ 4,000 rpm	Ground Clearance	6.7 in
Maximum Torque	21.4 lb-ft @ 2,400 rpm	Fuel Capacity	4.2 gal
Bore x Stroke	82.0 x 76.0mm	Turning Radius	11.8 ft
Compression Ratio	8.6:1	Cargo Bed Dimensions (LxWxH)	35.6 x 40.9 x 9.6 in
Fuel System	Fuel Injection	Cargo Bed Load Capacity	399 lb
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	Payload Capacity	884 lb
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock	Seating Capacity	2
Engine Braking	No	Towing Capacity	1,100 lb ^{***}
Alternator Output (max)	22.9 amp	Lighting	(4) LED headlights, tail/brake lights
CAPABILITY			
Front Suspension / Wheel Travel	MacPherson Strut/3.1 in	Overall Length	106.7 in
Rear Suspension / Wheel Travel	Unit Swingarm/3.1 in	Overall Width	52.6 in
Front Tires	26 x 9-12	Overall Height	75.0 in
Rear Tires	26 x 9-12	Estimated Dry Weight	1,058.4 lb ^{**}
Steering	Rack-and-pinion	Curb Weight	1,098.1 lb [*]
Front Brakes	Drum	Wheelbase	70.1 in
		Instruments	Fuel gauge, hour meter, oil temp light, parking brake light
		Color Choices	Metallic Onyx Black

Scan with camera to view videos, key features and more.

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

^{**}Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

^{***}Requires optional hitch.

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

All MULE SX™ Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE J1194.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.