

RIDGE® CREW LIFTED EDITION

A black and red Kawasaki Mule 4000T utility vehicle is shown from a front-three-quarter view. The vehicle features a black roll-over protection structure (canopy) and large, knobby tires. The body is primarily black with red accents, including a red stripe along the side and a red front bumper. The Kawasaki logo is visible on the front and side. The vehicle is parked on a white background.



SUNBEAM RED/SUPER BLACK

Engine	4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled
Displacement	999cc
Maximum Horsepower	116.0 hp ¹ @ 8,500 rpm
Maximum Torque	73.8 lb-ft @ 8,000 rpm
Bore x Stroke	73.4 x 59.0mm
Compression Ratio	10.6:1
Fuel System	EFI
Ignition	TCBI with Digital Advance
Starting System	Electric
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 4WD with locking front/rear differential, shaft
Engine Braking	Yes
Alternator Output (max)	85 amp
Electronic Rider Aids	Power Modes, Economical Riding Indicator

Front Suspension / Wheel Travel	Long-travel, Double wishbone, KYB shocks with piggyback reservoir, adjustable preload and compression damping/12.7 in
Rear Suspension / Wheel Travel	Long-travel, Double wishbone, KYB shocks with piggyback reservoir, adjustable preload and compression damping/12.7 in
Front Tires	ITP Cryptid 30 x 10-14
Rear Tires	ITP Cryptid 30 x 10-14
Steering	Rack-and-pinion w/ Electric Power Steering (EPS)
Front Brakes	Dual hydraulic 249mm discs with two-piston calipers
Rear Brakes	Dual hydraulic 249mm discs with single-piston calipers
Ground Clearance	14.2/14.6 in (max preload); 14.2 in CA Model
Fuel Capacity	12.9 gal

Turning Radius	19.0 ft
Cargo Bed Dimensions (LxWxH)	27.6 x 41.5 x 12.2 in
Cargo Bed Load Capacity	1,000/600 lb CA Model
Payload Capacity	1,559 lb
Seating Capacity	6-person (2 row), bench seats
Towing Capacity	2,500 lb
Lighting	All-LED lighting

Frame	Ladder type, tubular steel
Overall Length	156.3 in
Overall Width	64.0 in
Overall Height	82.9 in
Estimated Dry Weight	2,282.2/2,284.4 lb** CA Model
Curb Weight	2,392.4/2,394.6 lb* CA Model
Wheelbase	121.7 in
Instruments	Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Bluetooth indicator, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature)
Wheel Type	14" Aluminum
Additional Features	Elevated snorkel intakes and CVT exhaust duct, Raised fender flares, Brush guards, Cargo bed storage compartments, High-Density Polyethylene (HDPE) skid plates w/ drain holes, Rear view mirror, 4,500-lb winch with synthetic rope, Adjustable driver's seat, ERGO-FIT®, 8-in full-color TFT Instrumentation with Smartphone Connectivity via RIDELOGY THE APP Powersports, USB ports, QKR™ system compatible
Color Choices	Sunbeam Red/Super Black



*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
 *Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
 **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
 †This vehicle's HP was measured according to ISO standard 4066. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
 Specifications subject to change. Visit Kawasaki.com for full product details.