

2027

RIDGE® CREW ST HVAC

Kawasaki

Let the Good Times Roll®



MSRP

\$27,599

 METALLIC LIGHT GRAY



POWER		Details	
Engine	4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled	Ground Clearance	13.2/13.8 in (max preload); 13.2 in CA Model
Displacement	999cc	Fuel Capacity	12.9 gal
Maximum Horsepower	92.0 hp ¹ @ 8,500 rpm	Turning Radius	19.0 ft
Maximum Torque	65.8 lb-ft @ 5,500 rpm	Cargo Bed Dimensions (LxWxH)	34.6 x 49.0 x 12.8 in
Bore x Stroke	73.4 x 59.0mm	Cargo Bed Load Capacity	1,000/600 lb CA Model
Compression Ratio	10.6:1	Payload Capacity	1,444/1,290 lb CA Model
Fuel System	EFI	Seating Capacity	6-person (2 row), bench seats
Ignition	TCBI with Digital Advance	Towing Capacity	2,500 lb
Starting System	Electric	Lighting	All-LED lighting
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	DETAILS	
Final Drive	Selectable 4WD with locking rear differential, shaft	Frame	Ladder type, tubular steel
Engine Braking	Yes	Overall Length	156.7 in
Alternator Output (max)	85 amp	Overall Width	64.0 in
Electronic Rider Aids	Power Modes, Economical Riding Indicator	Overall Height	81.5 in
CAPABILITY		Estimated Dry Weight	2,352.7/2,354.9 lb** CA Model
Front Suspension / Wheel Travel	Long-travel, Double wishbone/12.7 in	Curb Weight	2,463.0/2,465.2 lb* CA Model
Rear Suspension / Wheel Travel	Long-travel, Double wishbone/12.7 in	Wheelbase	122.2 in
Front Tires	Duro 27 x 9-14	Instruments	Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Bluetooth indicator, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature)
Rear Tires	Duro 27 x 11-14	Additional Features	Full Cab with HVAC, Adjustable driver's seat, ERGO-FIT®, 7-in full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP Powersports, USB ports, QKR™ system compatible
Wheel Type	14" Aluminum	Color Choices	Metallic Light Gray
Steering	Rack-and-pinion w/ Electric Power Steering (EPS)		
Front Brakes	Dual hydraulic 249mm discs with two-piston calipers		
Rear Brakes	Dual hydraulic 249mm discs with single-piston calipers		

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.