

2027

TERYX KRX® 1000

Kawasaki

Let the Good Times Roll®



BASE MSRP

\$22,199[†]



SMOKY GRAY/SUPER BLACK

BASE MSRP \$22,199[†]



GRAYISH BLUE/SUPER BLACK

BASE MSRP \$22,199[†]

POWER			
Engine	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled	Ground Clearance	14.8 in (max) / 14.2 in (std)
Displacement	999cc	Fuel Capacity	10.6 gal
Maximum Horsepower	110.0 hp ¹ @ 8,500 rpm	Turning Radius	20.3 ft
Maximum Torque	75.2 lb-ft @ 7,000 rpm	Cargo Bed Dimensions (LxWxH)	14.6 x 33.1 x 9.1 in
Bore x Stroke	92.0 x 75.1mm	Cargo Bed Load Capacity	351 lb
Compression Ratio	11.5:1	Payload Capacity	781 lb
Fuel System	DFI® with (2) 50mm throttle bodies	Seating Capacity	2
Ignition	TCBI with electronic advance	Towing Capacity	N/A
Starting System	Electric	Lighting	(2) LED headlights, (2) LED taillights, LED stoplight
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)	DETAILS	
Final Drive	Selectable 2WD/4WD with locking front differential, shaft		
Engine Braking	Yes	Frame	Ladder type, tubular steel
CAPABILITY		Overall Length	130.1 in
Front Suspension / Wheel Travel	Double wishbone, Showa 2.5 shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/18.6 in	Overall Width	68.1 in
Rear Suspension / Wheel Travel	4-link trailing-arm rear suspension, Showa 2.5 shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/21.1 in	Overall Height	74.8 in
Front Tires	Maxxis® Carnivore 31 x 10.00R15 8PR	Estimated Dry Weight	1,794.9 lb** / 1,797.7 lb** CA Model
Rear Tires	Maxxis® Carnivore 31 x 10.00R15 8PR	Curb Weight	1,894.1 lb* / 1,896.3 lb* CA Model
Wheel Type	Alloy with bead-lock wheels	Wheelbase	98.8 in
Steering	Electric Power Steering (EPS) / rack-and-pinion	Instruments	Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp
Front Brakes	258mm dual hydraulic discs with 2-piston calipers	Additional Features	Skid plates w/ drain holes
Rear Brakes	258mm dual hydraulic discs with single-piston calipers	Color Choices	Smoky Gray/Super Black, Grayish Blue/Super Black

Scan with camera
to view videos,
key features
and more.



[†]Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.